

UX-TL CU OPRIRE AUTOMATĂ PENTRU JOASE PRESIUNI (0,4 MPa/4 Bar)

Model	Capacitate strângere diam. șurub mm	Cuplu Nm	Turatia în gol rpm	Lungime tot. mm	Greutate Kg	Dimensiune centru-exterior mm	Priza patrat in	Priza aer NPT	Tub aer Ø int. mm	Consum aer l/min	Nivel zgomot dB(A)
TIP PISTOL											
UX-TL700	6-8	15-28	7500	187	1,40	25	3/8"	1/4"	10,0	200	72
UX-TL800	8	20-32	7600	196	1,80	28	3/8"	1/4"	10,0	250	75
UX-TL900	8-10	30-48	7000	202	2,00	30	1/2"	1/4"	10,0	300	75
UX-TL1000	10	30-63	6300	207	2,30	33	1/2"	1/4"	10,0	350	75
UX-TL1300	10-12	50-95	5700	225	2,80	36	1/2"	1/4"	10,0	400	77
UX-TL1400	12-14	65-105	4500	245	3,40	40	1/2"	1/4"	10,0	450	79
UX-TL1620	14	110-170	4500	260	3,70	40	3/4"	1/4"	10,0	500	82
UXR-TL1820	14-16	120-200	4400	270	4,50	42	3/4"	3/8"	13,0	500	84
UXR-TL2000	16-18	170-280	3900	303	6,80	47	3/4"	3/8"	13,0	700	85

Presiune recomandată 0,4 MPa